# R4 Raythean Pawer 雷天动力设备 (苏州) 有限公司

## RAYTHEON POWER MACHINERY (SUZHOU) CO., LTD

# **Diesel Generator Set RCS115**



Photos reference only

### **Genset Technical Data**

Prime power	114kVA/90kW
Standby power	125kVA/100kW
Rated speed	1500 RPM
Output frequency	50 Hz
Phase	3
Rated voltage	400 V
Engine model(Cummins)	6BTA5.9-G2
Alternator model(Stamford)	UCI274D
Fuel consumption of 100% load	21 L/h
Fuel consumption of 75% load	16 L/h
Voltage regulation rate	≤±1%

#### **Prime Power**

This rating is for the supply of continuous electrical power (at variable load). There is no limit on the annual hours of operation and 10% overload power can be supplied for 1 hour in 12.

#### **Standby power**

This rating is for the supply of continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted.

#### Rated voltage


Subject to customer requirement

## **Advantages**

- ✓ High quality, reliable and complete power unit
- ✓ Compact design
- ✓ Easy start and maintenance possibility
- ✓ Every generating set is subject to a comprehensive test program which includes 50%, 75%, 100%, 110% load testing, checking and provision of all control and safety shut down functions testing
- ✓ The 24V high performance maintenance-free lead-acid starting battery including Rack and Cables
- ✓ Industrial capacity exhaust silencer and flexible exhaust
- ✓ With Chint Moulded Case Circuit Breaker (Up to1250A)
- ✓ Packing: be secured with polythene dust cover

## **Dimension and Weight**

Length (L)	mm	2250
Width (W)	mm	850
Height (H)	mm	1270
Weight	kg	1250
Tank capacity	L	215



## Chassis

- ✓ The complete gen-set is mounted as whole on a heavy-duty fabricated, steel base frame
- ✓ Anti-vibration pads are fixed between the engine/ alternator feet and the base frame
- ✓ Base frame design incorporates an 8-houres integral
- ✓ The generator set can be lifted or carefully pushed / pulled by the base frame
- ✓ Dial type fuel gauge and drain plug on the fuel tank

## Raytheon Power, your best global power partner

# RAYTHEON POWER MACHINERY (SUZHOU) CO., LTD

# **Engine**

Engine manufacturer		Cummins	
Engine model		6BTA5.9-G2	
Emissions statement			
Number of cylinders		6	
Cylinder arrangement		Vertical in-line	
Cycle		Four stroke	
Aspiration		Turbocharged & Aftercooled	
Bore×Stroke	mm×mm	102 x 120	
Displacement	Liter	5.9	
Compression Ratio		17.3:1	
Prime power/speed	kW/RPM	106/1500	
Standby power/speed	kW/RPM	116/1500	
Speed governor		Electrical	
Cooling system		Forced Water Cooling Cycle	
Steady speed droop	%	≤1%	
Total lubrication system capacity	L	16.4	
Coolant capacity (engine only)	L	10	
Fuel consumption at 100% load	g/kWh	211(at 1500RPM)	
Starter motor & Alternator		DC24V	

## Alternator

Design	Brushless, single bearing, flexible disc		
Protection grade	IP23		
Alternator cooling	Direct drive centrifugal blower fan		
Insulation grade	Class H		
Standard temperature rise	125°C		
Exciter type	Self-excited & AVR(Automatic Voltage Regulator)		
Power factor	0.8		
Rated voltage	380-415V(Subject to customer requirement)		
Voltage regulation rate	≤±1%		

## Alternator brand option

<b>Alternator Brand</b>	Alternator Model	Phase	Rated Speed	Rated Prime Power(kVA)
Stamford	UCI 274D	3	1500RPM	120
Leroy Somer	LSA 44.2S7	3	1500RPM	125
FARADAY	FD3B	3	1500RPM	120
Raytheon Power	WHI274D	3	1500RPM	120

Raytheon Power, your best global power partner



## R4 Raytheon Power 雷天动力设备(苏州) 有限公司

# RAYTHEON POWER MACHINERY (SUZHOU) CO., LTD

## **Control System**

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:

#### 1. Manual & Auto Start Control Panel

Panel equipment:

- ✓ The deepsea (UK original) control module
- ✓ Static battery charger
- ✓ Emergency stop push button

#### a) Generator set control module DSE4620 features:

- ✓ The module be utilised as a Manual or Auto Start Module for single gen-set applications
- ✓ Back-lit LCD display
- ✓ Remote start input
- ✓ Hours counter provides accurate information for monitoring maintenance and warranty periods
- ✓ Full engine monitoring and protection
- ✓ The module can be programmed using the front panel or by using the DSE Configuration Suite PC software
- ✓ 4 customizable Digital Inputs
- ✓ 4 customizable Outputs
- ✓ Easy push button control STOP/RESET -MANUAL -AUTO START

#### b) Parameters via LED display:

- ✓ Generator Volts (L-N)
- ✓ Generator Frequency (Hz)
- ✓ Engine speed
- ✓ Engine run time
- ✓ Battery volts

**DSE4620** 

#### c) Parameters display via the pointer instruments:

- ✓ Generator Ampere (L1,L2,L3)
- ✓ Engine oil pressure
- ✓ Engine water temperature

#### d) Alarms & Auto shutdown protect:

- ✓ Over and Under Speed
- ✓ Low and High Battery Volt
- ✓ Engine start failure
- ✓ Charge fail
- ✓ Over Current
- ✓ Under / Over Generator Voltage
- ✓ Low Oil Pressure
- ✓ Emergency stop
- ✓ High engine temperature

#### 2. Power Outlet Terminal Board Mounted on the Gen-set Base Frame

## The control modules option:



HGM6120



**DSE7320** 



DSE8610

Remarks: For the specific and detailed features of the above types, please refer to "Control System Selection" file.

## Raytheon Power, your best global power partner

# RAYTHEON POWER MACHINERY (SUZHOU) CO., LTD

# **Generator Set Options and Accessories**

Alternator
☐ PMG excitation
☐ Space heater
Low environment temperature
☐ Water heater
☐ Oil heater
☐ Battery heater
Control system
☐ AMF function
☐ ATS control cabinet
☐ Multiple generator automatic paralleling

#### RAYTHEON POWER MACHINERY (SUZHOU) CO., LTD

ADDRESS: No.599, Laixiu Road, Fenhu Economic Zone, Suzhou City,

Jiangsu Province, China

Tel: +86 21 52686721 Fax: +86 21 62772219

Email: <u>info@raytheonpower.com</u>
Web site: <u>www.raytheonpower.com</u>

DISTRIBUTED BY:		

©2013 by Raytheon Power, all right reserved.